


# 700-1700-1800 series AIR COUPLERS & PLUGS



**785**      **786**  
**788**      **789**



**787**



**783**      **784**



**S 782**



**783-4**      **786-4**  
**783-6**      **786-6**



**779**      **780**      **781**



**1786-4**      **1783-4**  
**1786-6**      **1783-6**

## T-TRU-FLATE/PARKER INTERCHANGE SERIES 1/4" BASIC SIZE

- T-style coupler bodies are brass
- T-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 40 SCFM
- Seals: Buna-N

WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.

## T-STYLE COUPLERS

Part No.	Connection
<b>785 / S 785</b>	1/4" NPT female
<b>786 / S 786</b>	1/4" NPT male
<b>787</b>	1/4" NPT female, oversize sleeve ring
<b>788</b>	3/8" NPT female
<b>789</b>	3/8" NPT male
<b>786-4</b>	1/4" hose barb
<b>786-6</b>	3/8" hose barb
<b>1786-4</b>	1/4" push on & lock hose barb
<b>1786-6</b>	3/8" push on & lock hose barb

## T-STYLE PLUGS

Part No.	Connection	Note
<b>783 / S 783</b>	1/4" NPT male	2/cd
<b>784 / S 784</b>	1/4" NPT female	2/cd
<b>783-4</b>	1/4" hose barb	
<b>783-6</b>	3/8" hose barb	
<b>779</b>	.305"-32 female re-capper plug	
<b>780</b>	.482"-26 female re-capper plug	
<b>781</b>	.482"-26 female Re-capper plug	2 3/4" long
<b>1783-4</b>	1/4" push on & lock hose barb	
<b>1783-6</b>	3/8" push on & lock hose barb	

## T-STYLE 1/4" COUPLER/PLUG KITS

Part No.	Contents
<b>S 782</b>	One #785 & one #783
<b>S 215</b>	One #785, one #784 & three #783, page 9

Replacement parts T-style:

**768** SYNTHETIC WASHER