

700-1700-1800 series AIR COUPLERS & PLUGS



P-STYLE TRU-FLATE/PARKER INTERCHANGE SERIES 3/8" BASIC SIZE

- P-style coupler bodies are heavy duty steel
- P-style plugs are case hardened steel plated to resist rust
- Bodies have 8 locking balls
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 68 SCFM
- Seals: Buna-N

WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.

P-STYLE COUPLER/PLUG KITS

Part No.	Contents
S 1802	one #1803 & one #1809 (1/4" NPT)

P-STYLE COUPLERS

Part No.	Connection
1803 / S 1803	1/4" NPT female
1804	1/4" NPT male
1805 / S 1805	3/8" NPT female
1806 / S 1806	3/8" NPT male
1806-6	3/8" hose barb
1746-6	3/8" push on & lock hose barb

P-STYLE PLUGS

Part No.	Connection	Description
1809 / S 1809	1/4" NPT male	2/cd
1810 / S 1810	1/4" NPT female	2/cd
1807 / S 1807	3/8" NPT male	2/cd
1808 / S 1808	3/8" NPT female	2/cd
1807-6	3/8" hose barb	
1747-6	3/8" push on & lock hose barb	

Replacement parts P-style:

1801 P-STYLE COUPLER REPAIR KIT

G-STYLE TRU-FLATE/PARKER INTERCHANGE SERIES 1/2" BASIC SIZE

- G-style coupler bodies are steel, plated to resist rust
- G-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 99 SCFM
- Seals: Buna-N

WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.

G-STYLE COUPLERS

Part No.	Connection
1813	3/8" NPT female
1814	3/8" NPT male
1815 / S 1815	1/2" NPT female
1816 / S 1816	1/2" NPT male

G-STYLE PLUGS

Part No.	Connection
1819	3/8" NPT male
1820	3/8" NPT female
1817 / S 1817	1/2" NPT male
1818 / S 1818	1/2" NPT female

Note: G-style couplers will work with G-style Industrial Interchange & Parker/Tru-Flate plugs.

Replacement parts G-style:

1811 G-STYLE COUPLER REPAIR KIT



S 1802



1803
1805



1804
1806



1806-6



1747-6



1746-6



1807
1809



1807-6



1808
1810



1813
1815



1814
1816



1817
1819



1818
1820