



**L-STYLE LINCOLN INTERCHANGE SERIES 1/4" BASIC SIZE**

- L-style couplers are push type
- L-style couplers are steel, plated to resist rust
- L-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 32 SCFM
- Seals: Buna-N

WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.

**L-STYLE COUPLERS**

Part No.	Connection
<b>790 / S 790</b>	1/4" NPT female
<b>794</b>	1/4" NPT male

**L-STYLE PLUGS**

<b>791 / S 791</b>	1/4" NPT male	2/cd
<b>792 / S 792</b>	1/4" NPT female	2/cd



**790**

**794**



**791**

**792**

**D-STYLE DIAMOND-U INTERCHANGE SERIES 1/4" BASIC SIZE**

- D-style couplers are steel, plated to resist rust
- D-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 34 SCFM
- Seals: Buna-N

**D-STYLE COUPLERS**

Part No.	Connection
<b>795</b>	1/4" NPT female
<b>796</b>	1/4" NPT male

**D-STYLE PLUGS**

<b>797</b>	1/4" NPT male
<b>798</b>	1/4" NPT female



**795**

**796**



**797**

**798**

WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.