



TWIST-LOCK UNIVERSAL COUPLERS

- Twist lock couplers are malleable iron
- Commonly referred to as “Crowfoot” or “Claw” type couplers
- Milton twist lock couplers come complete with safety clip and lanyard
- Maximum working pressure: 150 PSI
- Maximum temperature: 160° F
- 1/4” through 1” universal couplers can be used together.
1 1/4”, 1 1/2” and 2” cannot be used with the smaller sizes.
- Application: Construction, highway maintenance, mobile compressors, mining, agriculture, tool rental shops

WARNING: TWIST LOCK COUPLERS ARE NOT FOR STEAM OR HYDRAULIC APPLICATIONS.

Part No.	Connection
1862-4	3/8” hose barb
1862-6	1/2” hose barb
1862-8	3/4” hose barb
1862	1” hose barb
1862-10	1 1/4” hose barb
1862-12	1 1/2” hose barb
1862-14	2” hose barb
<hr/>	
1863-2	1/4” NPT male
1863-4	3/8” NPT male
1863-6	1/2” NPT male
1863-8	3/4” NPT male
1863	1” NPT male
<hr/>	
1864-2	1/4” NPT female
1864-4	3/8” NPT female
1864-6	1/2” NPT female
1864-8	3/4” NPT female
1864	1” NPT female
1864-10	1 1/4” NPT female
1864-12	1 1/2” NPT female
1864-14	2” NPT female

Replacement Parts Universal Twist Lock Couplers:

- 1865-1** SAFETY CLIP FOR UNIVERSAL TWIST LOCK COUPLERS
- 1865-2** LANYARD
- 1865-3** RUBBER REPLACEMENT WASHER FOR TWIST LOCK COUPLERS



1862
1862-4
1862-6
1862-8
1862-10
1862-12
1862-14



1863
1863-2
1863-4
1863-6
1863-8



1864
1864-2
1864-4
1864-6
1864-8
1864-10
1864-12
1864-14



1865-2



1865-1



1865-3