

2400 series CLEAR REINFORCED PVC TUBING

CLEAR REINFORCED PVC TUBING

Also known as PVR tubing. It's lightweight, flexible, transparent, easy to clean, and resists ozone and most chemicals. FDA approved. Can be used with hose barbs, ferrules and hose clamps for such applications as manufacturing equipment, water, lubrication, packaging machines, food and beverage equipment, plastic molding industry.

- Working temperature range: 25° F to 122° F
- Material: Thermoplastic PVC reinforced with spiral polyester yarn
- Color: Clear



2400

CLEAR REINFORCED PVC TUBING (BULK NO FITTINGS)

Part No.	Length	Hose ID	Hose OD	Max working pressure @ 70° F
2440-300	300'	1/4"	0.438"	250 PSI
2440-500	500'	1/4"	0.438"	250 PSI
2460-300	300'	3/8"	0.594"	225 PSI
2460-500	500'	3/8"	0.594"	225 PSI
2480-300	300'	1/2"	0.750"	200 PSI
2480-500	500'	1/2"	0.750"	200 PSI

CLEAR REINFORCED BULK PVC TUBING LENGTHS

Part No.	Length	Hose ID	Max working pressure @ 70° F
2440-25	25'	1/4"	250 PSI
2440-50	50'	1/4"	250 PSI
2460-25	25'	3/8"	225 PSI
2460-50	50'	3/8"	225 PSI
2480-25	25'	1/2"	200 PSI
2480-50	50'	1/2"	200 PSI