

2600 series FLEX-LITE HOSE



FLEX-LITE HOSE

Soft, light weight, flexible polyurethane hose made to withstand rugged outdoor use and resist abrasions. Combines all the advantages of polyurethane hose and 2 braid heavy duty rubber hose. Flex-lite polyurethane hose is nylon reinforced and remains soft and flexible at extreme temperatures of -40° F to +210° F. Non-kinking, and lightweight ideal for air tools, impact tools, staplers, roofers, construction, automotive service station, industrial, manufacturing plants, mining, farm use, fleet, paint shops and paint & body applications. Flex-Lite Hose has a minimum bend radius of 2.25”.

- Assembled with PVC strain relief
- Assembled with 1/4” NPT swivel fittings
- Maximum working pressure: 200 PSI
- Burst pressure: 800 PSI

FLEX-LITE REELS

Part No.	Hose ID	Length
2604-300	1/4”	300’
2606-300	3/8”	300’

FLEX-LITE ASSEMBLIES

- Assembled with PVC strain relief
- Assembled with male NPT swivel fittings

Part No.	Hose ID	Length	Connection
2604-25	1/4”	25’	1/4”
2604-50	1/4”	50’	1/4”
2604-100	1/4”	100’	1/4”
2606-25	3/8”	25’	1/4”
2606-50	3/8”	50’	1/4”
2607-25	3/8”	25’	3/8”
2607-50	3/8”	50’	3/8”

FLEX-LITE ACCESSORIES

Part No.	Description
2614	1/4” male NPT swivel fittings with PVC strain relief
2616	3/8” x 1/4” NPT male swivel fittings with PVC strain relief
2618	3/8” x 3/8” NPT male swivel fittings with PVC strain relief