

2700 series HOSE REELS



2740-33
2760-25
2760-33
2760-50
2760-65
2780-33
2780-50

Factory lubricated bearing hubs for years of dependable service. Beaded edges on reels prevent hose damage or injury to user. Solid 12 gauge mounting plate to attach to surfaces such as walls, benches and pressure washer frames. Hidden latch mechanism helps prevent build-up of grime and debris. Complete with heavy duty 2 braid 4 spiral hose. Spring loaded, self-retracting reels.

- Maximum working pressure: 300 PSI
- Maximum working temperature: 200° F (93° C)

Part No.	Hose ID	Length	Fittings NPT (female inlet, male outlet)
2740-33	1/4"	33'	1/4" both ends
2760-25	3/8"	25'	3/8" both ends
2760-33	3/8"	33'	3/8" inlet, 1/4" outlet
2760-50	3/8"	50'	3/8" inlet, 1/4" outlet
2760-65	3/8"	65'	3/8" inlet, 1/4" outlet
2780-33	1/2"	33'	1/2" both ends
2780-50	1/2"	50'	1/2" both ends



2765-150
2785-65

HAND CRANK HOSE REELS

Factory lubricated bearing hubs for years of dependable service. Beaded edges on reels prevent hose damage or injury to user. Hidden latch mechanism to prevent build-up of grime and debris. Removable handle can be mounted on either side. Spring brake keeps hose from unwinding. Hose not included.

- Maximum working pressure: 300 PSI
- Maximum working temperature: 200° F (93° C)
- #2765-150 supplied with 1/4" NPT adapters

Part No.	Hose ID	Hose length capacity
2765-150	3/8" hose	150'
2785-65	1/2" hose	65'